

Job: _____

Job Site: _____ State: _____ Client Name: _____

Notes: _____ Approvals: _____ Date: _____

PRODUCT DESCRIPTION

Pole Configuration: Our security camera poles can be drilled to meet your specifications. The drill pattern, location and orientation need to be provided by the customer. A removable top cap or tenon is provided. The most common tenon option is a 2-3/8 inch diameter tenon; however, other options are available.

Pole Shaft: Our commercial grade fiberglass round tapered security camera poles are constructed of thermoset polyester resin containing "E" type fiberglass. The smooth surface consists of a saturated polyester surfacing veil and an unsaturated polyester resin layer containing UV inhibitor and pigment throughout.

Handhole: A 2-1/2 x 5 inch reinforced handhole is provided at 26.5 inches from the base. A cover with a single screw to secure the latch mechanism is also provided.

Base Plate and Cover: A galvanized steel base plate is permanently bonded to the pole shaft. A 2 piece fiberglass base cover is provided to cover the anchor bolts after installation.

Anchor Bolts: A set of 4 steel anchor bolts are provided with each pole assembly. Each bolt includes 2 nuts and 2 washers. The top of the anchor bolt is threaded for securing and leveling the pole with the provided nuts and washers. An actual size paper anchor bolt template is provided.

Color Options: Bronze, black, white and gray colors are provided at no extra charge. Custom color options are available at a surcharge.

Other Options: The following options are available; custom colors, custom pole heights, additional handholes and custom base plate dimensions. Please consult one of our security camera pole experts for details.

SPECIFICATION TABLE					
Side Mount			Top Mount		
Mounting Height (ft.)	A	25	Mounting Height (ft.)	A	25
Top Diameter (in.)	B	5.2	Top Diameter (in.)	B	4.41
Butt Diameter (in.)	C	9.81	Butt Diameter (in.)	C	9.81
Bolt Circle (in.)	D	13.5	Bolt Circle (in.)	D	13.5
Anchor Bolts (in.)	E	1 x 36 x 4	Anchor Bolt (in.)	E	1 x 36 x 4

MAXIMUM EPA WITH 1.3 GUST FACTOR					
Side Mount			Top Mount		
80 mph:	8.3	Square Feet	80 mph:	7.5	Square Feet
100 mph:	5.2	Square Feet	100 mph:	5.0	Square Feet
120 mph:	5.2	Square Feet	120 mph:	5.0	Square Feet

