

Job: _____

Job Site: _____ State: _____ Client Name: _____

Notes: _____ Approvals: _____ Date: _____

PRODUCT DESCRIPTION

Pole Configuration: Our security camera poles can be drilled to meet your specifications. The drill pattern, location and orientation need to be provided by the customer. A removable top cap or tenon is provided. The most common tenon option is a 2-3/8 inch diameter tenon; however, other options are available.

Pole Shaft: Our commercial grade fiberglass square security camera poles are constructed of thermoset polyester resin containing "E" type fiberglass. The smooth surface consists of a saturated polyester surfacing veil and an unsaturated polyester resin layer containing UV inhibitor and pigment throughout.

Handhole: A 2-1/2 x 5 inch reinforced handhole is provided at 18 inches from the base. A cover with a single screw to secure the latch mechanism is also provided.

Base Cover: A 2 piece fiberglass base cover is included.

Anchor Bolts: A set of 4 steel anchor bolts are provided with each pole assembly. Each bolt includes 2 nuts and 2 washers. The top of the anchor bolt is threaded for securing and leveling the pole with the provided nuts and washers. An actual size paper anchor bolt template is provided.

Color Options: Bronze, black, white and gray colors are provided at no extra charge. Custom color options are available at a surcharge.

Other Options: The following options are available; custom colors, custom pole heights, additional handholes and custom base plate dimensions. Please consult one of our security camera pole experts for details.

SPECIFICATION TABLE		
Mounting Height (ft.)	A	25
Top Square (in.)	B	4
Butt Square (in.)	C	4
Bolt Circle (in.)	D	10.25
Anchor Bolt Size (in.)	E	5/8 x 21 x 3
Bolt Circle Range (in.)	-	8-12.5
Pole Weight (lbs.)	-	57

MAXIMUM EPA WITH 1.3 GUST FACTOR		
90 mph:	3.8	Square Feet
100 mph:	2.1	Square Feet
110 mph:	0.8	Square Feet
-- mph:	--	Square Feet

