

**30A66SS250S**

30 Foot Square Straight Aluminum Security Camera Pole, 6.6 Inch Wide, 0.250 Inch Wall Thickness

Job: _____

Job Site: _____ State: _____ Client Name: _____

Notes: _____ Approvals: _____ Date: _____

PRODUCT DESCRIPTION

Pole Configuration: Our security camera poles can be drilled to meet your specifications. The drill pattern, location and orientation need to be provided by the customer. A removable top cap or tenon is provided. The most common tenon option is a 2-3/8 inch diameter tenon; however, other options are available.

Pole Shaft: The pole shaft is constructed of seamless extruded tube of 6063-T6 aluminum alloy per the requirements of ASTM B221. The shaft assembly is full-length heat treated to produce a T6 temper.

Handhole: A handhole with grounding provision is provided at 18 inches from the base end of the pole assembly. Each handhole includes a cover and the attachment hardware.

Base Cover: A 4-bolt cast aluminum base flange of alloy 356-T6 with aluminum bolt covers and stainless steel attaching screws.

Anchor Bolts: A set of 4 galvanized steel anchor bolts are provided with each pole assembly. Each bolt includes 2 nuts and 2 washers. The top of the anchor bolt is threaded for securing and leveling the pole with the provided nuts and washers. An actual size paper anchor bolt template is provided.

Color: Commercial grade, durable powder coat is the standard option. Dark bronze, gray, green, white and black colors are provided at no additional charge. Custom color options are available at a surcharge.


Other Options: The following options are available. Please consult one of our security camera pole experts for details: Vibration damper, custom tenon sizes, custom colors, electric/GFI outlets, custom pole heights, additional handholes and custom base plate dimensions.

SPECIFICATION TABLE


Mounting Height (ft.)	A	30
Wall Thickness (in.)	B	0.250
Top Square (in.)	C	6.6
Bottom Square (in.)	D	6.6
Base Square (in.)	E	13.5
Bolt Circle (in.)	F	13.5
Bolt Projection (in.)	G	2.25
Anchor Bolt Size (in.)	H	1 x 36 x 4
Bolt Circle Range (in.)	-	13-14

MAXIMUM EPA WITH 1.3 GUST FACTOR

90 mph:	19.0	Square Feet
100 mph:	13.0	Square Feet
110 mph:	11.4	Square Feet
120 mph:	7.6	Square Feet



Base Plate with Snap-In Bolt Covers



(4) Anchor Bolts

