

QS10S4SQ125

10 Foot Square Steel Light Pole, 4 Inch Width, 11 Gauge, Dark Bronze, Quick Ship

Product Description

- **Pole Top Options:** A removable plastic pole cap is provided if the pole is drilled for attaching light fixtures. The drill pattern and drill orientation needs to be provided by the customer unless Energy Light fixtures are used for the project. If a tenon option is selected, a steel tenon will be provided. A 2 ³/₈ inch diameter tenon with a 4 inch length is standard; however, the customer needs to confirm the appropriate tenon size required for the project.
- **Pole Shaft:** Commercial quality welded steel tubing of 1 piece construction with a minimum yield strength of 55,000 psi is used to fabricate the pole shaft.
- **Handhole:** 3 × 5 inches tall reinforced handhole is provided at 18 inches from the base. A cover with a single screw to secure the latch mechanism is also provided.
- **Base Cover:** A 2 piece metal base cover is provided along with hardware to securely attach the 2 pieces together after pole installation.
- Anchor Bolts: A set of 4 galvanized steel anchor bolts is provided with each pole assembly. Each bolt includes 2 nuts and 2 washers. A portion of the anchor bolt is threaded for securing and leveling the pole with the provided nuts and washers. An actual size paper anchor bolt template is included.
- Color: Dark Bronze





Specification Table				
Mounting Height (ft.)	Α	10		
Gauge	В	11		
Top Width (in.)	С	4		
Butt Width (in.)	D	4		
Base Width (in.)	Е	10.5		
Bolt Circle (in.)	F	8.5		
Bolt Projection (in.)	G	3.75		
Base Thickness (in.)	Н	0.75		
Anchor Bolt Size (in.)	Ι	$0.75 \times 17 \times 3$		
Bolt Circle Range (in.)	-	8-11		
Pole Weight (lbs.)	_	76		

Maximum EPA with 1.3 Gust Factor:			
90 mph:	21.5	Square Feet	
100 mph:	17	Square Feet	
110 mph:	14	Square Feet	
120 mph:	11.5	Square Feet	

