

QS25S4RS125

25 Foot Round Straight Steel Light Pole, 4 Inch Diameter, 11 Gauge, Quick-Ship

PRODUCT DESCRIPTION

Pole Top Options: Light Poles are provided with either a removable metal top cap or a welded 2-3/8 inch steel tenon. Poles with a top cap are pre-drilled on 2 sides at 180 degrees.

Pole Shaft: The 4 inch diameter shaft has a minimum yield strength of 46,000 psi.

Handhole: A 3 inch wide by 5 inch tall reinforced handhole is located 16-1/2 inches from the base plate of the pole. A matching, removable cover and attachment hardware are included. Ground lug and ground wire are also included.

Base Cover: A 2 piece, powder coated, heavy duty steel base cover is included. Metal screws are also included to securely attach the 2 pieces together after pole installation.

Anchor Bolts: A set of 4 fully galvanized steel anchor bolts is provided with each pole assembly. Each anchor bolt includes 2 nuts and 2 washers. The top portion of the anchor bolt is threaded for securing and leveling the pole with the provided nuts and washers. An actual size paper anchor bolt template is also provided.

Color: Commercial grade, durable bronze powder coat.

Specification Table		
Mounting Height (ft.)	A	25
Gauge	B	11
Top Diameter (in.)	C	4
Butt Diameter (in.)	D	4
Base Thickness (in.)	E	0.75
Base Width (in.)	F	8
Bolt Circle (in.)	G	8.5
Bolt Projection (in.)	H	3.75
Handhole Cover (in.)	I	3 x 5
Anchor Bolt Size (in.)	J	0.75 x 18.75 x 3
Pole Weight (lbs.)	-	143.3

Maximum EPA with 1.3 Gust Factor:		
70 mph:	4.5	Square Feet
80 mph:	2.4	Square Feet
90 mph:	1.1	Square Feet
100 mph:	0.1	Square Feet

